

07420.N TIMED TAP FOR WASHBASIN

GENERAL DATA



- Cold/hot timed water tap for washbasin.
- Model for installation in washbasin or countertop.
- Opening with push button.
- Interchangeable cartridge that includes the timed mechanism.
- Robust construction in chromed brass.
- Timed to 7 ± 3 seconds.
- Elements of subsection included.

TECHNICAL DATA

- Material: CW617N brass chrome body.
- Cartridge material: CW617N chrome-plated brass push button + plastic components in POM.
- Chrome under standard EN248.
- Cartridge thread dimensions: M 28 x 1.5 mm.
- Flow at 3 bar: 6 l/min.
- Operation time: 7 ± 3 s according to the UNE-EN 8016.
- T^a maximum 85 °C.
- T^a maximum recommended 60 °C.
- Maximum pressure: 5 bar.
- Minimum pressure: 0.5 bar.
- Recommended pressure: 3 bar.
- Exchangeable Aerator M 24 x 1 mm.
- Plastic particle filter included.

SUGGESTED TEXT FOR PRESCRIPTION

Cold/hot timed water tap for washbasin NOFER 07420.N with push button for installation on countertop. It assembles a self-closing cartridge timed to 7 ± 3 s made in chrome plated brass plus plastic components in POM. The body is also made of chromed cast brass. Fixed spout with replaceable aerator M24. Flow rate of 6 l/min with 3 bars of dynamic pressure. Includes filter and all accessories for installation. Dimensions: 135.3 mm height x 135.2 mm width. Manufactured by NOFER, S.L. – Avda. de la Fama, 118 - c.p: 08940 Cornellà de Llobregat - Barcelona. www.nofer.com.

TECHNICAL DRAWING

